IntoPrint



The SP1360 is the ideal printer for specialty graphics, short run production, and creative design firms. Offering unrivaled media handling including envelopes, labels, films, and more, the SP1360 gives you the flexibility to meet your customer's ever changing needs. With the capability to print up to 360 gsm single sided, or up to 320 gsm duplexed, the SP1360 has one of the widest ranges of media selections available. Vibrant and sharp image quality means the SP1360 gives you professional level output in an affordable package. Print resolutions up to 1200x1200 ensure every detail of your design is reproduced accurately. The SP1360 offers print speeds up to 60 ppm for both mono and color prints, giving you the ability to offer quick turn around times for today's demanding customers.

- LED printheads control the amount of toner applied to each 1200-dpi dot, preserving fine image detail and maximizing color fidelity
- End user replaceable consumables ensures minimum down time
- Single pass color technology improves color registration for all paper types and weights
- Printer control system adjusts for sharp, clear images every time
- High print speeds of up to 60 ppm color and mono
- Low total cost of ownership (TCO)

The SP1360 is perfect for a general office printer that performs like a production press. Take your presentations and print proofs to the next level, with the SP1360's excellent image quality and fast print speeds.

For commercial print shops, the SP1360 is the perfect complement to a full production CMYK machine. Give your business the extra capacity needed to offer customers cost-effective personalized printing, on the media of their choice without interrupting the workflow of your full production machine. Extend the capabilities of your business using the SP1360 printer to manage specialized short-run requests that require unique media or quick turn arounds.



Specifications

| Print Speed | CMYK/Mono | 60 ppm Letter-size sheets, 27 ppm Tabloid sheets |
|--------------------------------|------------------------------------|---|
| Time to First Page | CMYK/Mono | Approx. 8 seconds |
| Duty Cycle | Printers | 300,000 pages max per month |
| Print Quality | Resolution | Up to 1200 x 1200 dpi; ProQ 1200 x 600 x 16 levels |
| Memory | RAM (Standard/Max) | 2 GB |
| | Processor | 1.2 GHz ARM CPU |
| Compatibility | Printer Languages | Adobe® PostScript 3TM, PCL® 6, PCL 5c, XPS® |
| | Connectivity | High-speed USB 2.0, 10 Base-T/100 Base-TX/1000 Base-T Ethernet |
| | Operating Systems | Windows 10, Windows® 8, Windows 7, Windows Vista®, Windows XP, Windows Server 2012, Windows Server 2008, Windows Server 2008 R2, Windows Server 2003; Mac® OS 10.3.9 – 10.9 |
| | Network Protocols | TCP/IP, EtherTalk |
| Color Features/ Solu- tions | Standard | PostScript®driver supports trapping; Embedded ICC Profile-based workflow; Simu- lations for SWOP, ISO Coated, Japan Color; PDF Direct Print; PS Gamma Adjust; and Color Correct |
| Media Handling | Media Sizes | Trays 1 & 2: Up to 12.00" x 18.00" Multi-purpose Tray: Min 2.52" x 3.50" up to 13.00" x 52.01" |
| | Media Weight | Trays 1 & 2 : 52–320gsm Multi-purpose Tray: 80–360gsm |
| Media Capacity | Multi-purpose Tray | Up to 310 sheets |
| | Trays 1 & 2 | Up to 580 sheets each |
| | High-Capacity Feeder (Optional) | Up to 1740 sheets (3 trays, 580 sheets each) |
| Media Output | Face Down | Max 610 sheets |
| | Face Up | Max 300 sheets |
| Environmental | Size (WxDxH) | 27.5" x 26.18" x 25.2" (699 mm x 665 mm x 640 mm) |
| | Weight | 215.2 lb. (97.6 kg) including consumables |
| | Temperature/Humidity | 50° – 90° F (10° – 32° C) / 20% – 80%RH |
| | Power Consumption | 115V 15A Active 1600W max. /1100W avg.; Standby avg. 40W; PowerSave mode 30W or less; Sleep mode 4W or less; Auto Shutoff 0.4W or less. |
| | Noise Levels | Printer: Active 57dBA or less; Standby 34dBA or less; PowerSave mode – Inaudible |
| Warranty | Limited | l year warranty |
| | | |