Copystar
Kyocera Technology

› PRINT › COPY › SCAN › FAX

CS 306ci

COLOR MULTIFUNCTIONAL
SYSTEM

BIG POWER
NOW COMES IN
A SMALLER SIZE.

The Copystar CS 306ci brings affordable color to document imaging, offering scalable features, output speeds up to 32 ppm and print, copy, scan and fax capability, all in a compact footprint. An intuitive 4.3" color TSI powers productivity with easy access to features and functionality, while a full suite of optional Business Applications takes productivity to new levels. Combined with proven KYOCERA long-life technology and reliability, the Copystar CS 306ci is the smart choice for your evolving business needs.

› Color Output up to 32 Pages per Minute in Color and Black
› Standard Print, Copy, and Scan
› Standard 75 Sheet Document Processor
› KYOCERA Business Applications Capable
› Standard USB Host Interface for On-the-Go Printing and Scanning
› Space-Saving Optional 300-Sheet Internal Finisher
› Standard 600 Page Capacity Can Be Expanded up to 3,100 Pages to Support Longer Jobs
› Wireless Printing and Scanning Capable
› Apple AirPrint™ & KYOCERA Mobile Print Compatible for a Mobile Printing Solution

Copystar
Kyocera Technology

BASIC SPECIFICATIONS

Configuration: Color Multifunctional System – Print/Scan/Copy/Optional Fax

Pages Per Minute:
Color and Black – Letter: 32 ppm, Legal: 26 ppm, A4: 30 ppm

Warm Up Time: 20 Seconds or Less (Power On)

First Page Out:
Copy: 6.4 Seconds or Less Black, 7.8 Seconds or Less Color;
Print: 7.0 Seconds or Less Black, 8.0 Seconds or Less Color

Display: 4.3" Color Touch Screen Control Panel

Resolution: 600 x 600 dpi; 9600 dpi x 600 dpi

Memory: 1GB Standard (2GB Maximum)

Hard Disk Drive: Optional 32GB (**HD-6**) or 128GB (**HD-7**) SSD

Duplex: Standard Stackless Duplex Supports Statement to Legal (5.5" x 8.5" – 8.5" x 14"), 16 lb Bond – 120 lb Index (60 – 220gsm)

Standard Output Tray: Statement - Legal / 500 Sheets

Electrical Requirements:
120V, 60Hz, 9.5A; 220-240V, 50Hz, 5.0A

Typical Electricity Consumption (TEC):
120V: 1.8 kWh/week; 220V: 1.7 kWh/week

Dimensions: 21.65" W x 19.96" D x 29" H (includes RADF)

Weight: 101.41 lbs (includes Standard RADF)

Maximum Monthly Duty Cycle: 100,000 Pages per Month

PAPER SUPPLY

Standard Paper Sources:
Single 500 Sheet Tray, 100 Sheet MPT

Optional Paper Sources:
500 Sheet Tray (**PF-5120**), Dual 500 Sheet Trays (**PF-5130**)[1];
2,000 Sheet Large Capacity Tray (**PF-5140**)[1]

Paper Capacity:
Standard: 600 Sheets;
Maximum: 3,100 Sheets

Paper Size:
Tray 1 – **PF-5120** and **PF-5130**: 5.5" x 8.5" – 8.5" x 14" (Statement to Legal); **PF-5140**: 8.5" x 11";
MPT: 5.5" x 8.5" – 8.5" x 14" (Multiple Sheets)

Paper Weight:
Trays/MPT: 16 lb Bond – 120 lb index (60 – 220gsm)

Input Materials:
Standard/Optional Drawer: Plain Paper, Bond Paper, Recycled Paper, Envelopes;
MPT: Plain Paper, Bond Paper, Recycled Paper, Cardstock, Transparencies, Labels, Envelopes

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication, IPsec, SNMPv3, IEEE802.1x, IPP over SSL/TLS, HTTPS, FTP over SSL/TLS, SMTP over SSL/TLS, POP3 over SSL/TLS, Enhanced WSD over SSL/TLS, LDAP over SSL/TLS

Optional: Data Security Kit (E): HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATION

Standard Controller: Main: SoC (PPC465S) 1 GHz

PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL/PCL5c), KPDL3 (PS3), XPS, OPEN XPS

Print Resolution: 600 x 600 dpi

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

OS Compatibility: Windows: 7/8/8.1/Server 2003/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2
Mac: OS Compatibility: Mac OS 10.5 and later, AirPrint Enabled

Mobile Printing: Apple AirPrint, KYOCERA Mobile Print

Interfaces:
Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 2 USB Host Interfaces, 2 Expansion Slots;
Optional: 10/100/1000BaseTX (**IB-50** for Dual NIC);
Optional: IEEE 802.11 b/g/n (**IB-51** for Wireless LAN Interface)

Network Print and Supported Protocols:
TCP/IP, IPv4, IPv6; HTTP, LPD, FTP, IPP, RawPort, LLTD, SNTP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print

Drivers: KX Driver, PCL Mini Driver, KPDL Mini Driver, KX Driver for XPS, Network Fax Driver, TWAIN Driver, WIA Driver, PPD for MAC, PPD for Linux

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, Command Center RX

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner

Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

Scan Speeds (mono/color) @ 300 dpi:
DP-5100: Simplex: 40 ipm BW/30 ipm Color;
Duplex: 17 ipm BW/13 ipm Color

Connectivity / Supported Protocols:
10/100/1000BaseTX, TCP/IP, Hi-Speed USB 2.0

Scanning Functions: Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

Original Size:
Through DP: Statement to Banner (5.5" x 8.5" – 8.5" x 74.8");
Glass: up to 8.5" x 14"

Drivers: TWAIN/WIA Driver

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi

Image Mode: Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1 – 999 / Auto Reset to 1

Additional Features: Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Interrupt Copy

Job Management: 100 Department Codes

Magnification / Zoom: Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25-400% in 1% step increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

STANDARD DOCUMENT PROCESSOR

Type / Capacity: Standard Reversing Automatic Document Processor / 75 Sheets

Acceptable Originals: 5.5" x 8.5" – 8.5" x 74.8" (1900mm)

Acceptable Weights:
DP-5100: Simplex: 13 – 32 lb Bond (50 – 120gsm);
Duplex: 13 – 32 lb Bond (50 – 120gsm)

OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System 11

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG

Transmission Speed / Modem Speed:
Less than 3 seconds / 33.6 Kbps

Fax Memory: 8 MB

Driver: Network Fax Driver

Fax Functions: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

OUTPUT & FINISHING OPTIONS

OPTIONAL 300 SHEET INTERNAL FINISHER DF-5100[2]

Stack / Staple Capacity: 300 Sheets / 50 Sheets (up to 24 lb Bond (90gsm))

Paper Size: 5.5" x 8.5" – 8.5" x 14"

Paper Weight: 16 lb Bond – 120 lb Index (60 – 220gsm)

Edge Staple Position: 3 Positions: Front 1 staple, Edge 1 staple, Face 2 staple

Dimensions: 19.13" W x 15.55" D x 6.22" H

OPTIONAL MULTI-BIN MAILBOX MT-5100[2,3]

MT-5100 includes 5 Trays;
Supports 16 lb Bond – 90 lb Index (60 – 163gsm);
Stack Capacity per bin: 100 sheet: 5.5" x 8.5", 8.5" x 11";
50 sheet: 8.5" x 14" (20 lb. Bond)

Paper Size: 5.5" x 8.5" – 8.5" x 14"

Paper Weight: Tray A: 16 lb Bond – 120 lb Index (60 – 220gsm);
Mail Tray: 16 lb Bond – 90 lb Index (60 – 163gsm)

Stack Capacity:
Tray A: 500 sheet (5.5" x 8.5", 8.5" x 11"); 250 sheet (8.5" x 14")
Mail tray: 100 sheet (5.5" x 8.5", 8.5" x 11"); 50 sheet (8.5" x 14")

Dimensions: 16.30" W x 14.17" D x 29.92" H

ADDITIONAL OPTIONS

Bridge Unit Attachment Kit (**AK-5100**), Job Separator[2] (**JS-5100**), Internet Fax Kit (A), Card Authentication Kit (B), Gigabit NIC (**IB-50**), IEEE802.11b/g/n (**IB-51**), ThinPrint (**UG-33**), Document Tray (**DT-5100**), Card Reader Holder (F), SD Card[4] (16 or 32GB)

[1] Requires PF-5120
[2] Only 1 output option can be installed
[3] Requires Bridge Unit Attachment Kit (AK-5100)
[4] Optional SD Card Required for HyPAS Business Applications

ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? KYOCERA offers a robust portfolio of Business Applications that seamlessly and securely integrate with our MFPs. To learn more about which Business Applications are right for your business, visit the Solutions section on our website.

AirPrint · ENERGY STAR · R6 READY · Java POWERED · Compatible with Windows 7 · Mac

Copystar
Kyocera Technology